

# › Kleinststeuerungen em4 & Millenium Evo Schnittstelle Speicherschnittstelle

- › Kopieren Sie Ihr Anwendungsprogramm von einer SPS in eine andere.
- › Endprogramme für Ihre Kunden
- › Firmware-Aktualisierung





Speicherschnittstelle

Spezifische Eigenschaften	
Bestell-Nr.	88 980 114
Ausführung	Glossy black
Farbe	Black RAL 9011
Werkstoff	UL94 V0, 1272/2008/CE (Halogen free)
Allgemeine Kenndaten	
Produktzertifizierungen	CE, cURus Listed
Erfüllt die Anforderungen der EMV-Richtlinie (gemäß 2014/30/EU)	IEC/EN 61000-6-1 (Residential, commercial and light-industrial environments) IEC/EN 61000-6-2 (Industrial) IEC/EN 61000-6-3 (Residential, commercial and light-industrial environments) IEC/EN 61000-6-4 (Industrial)
Betriebstemperatur	-20 (-4 °F) → +60°C (140 °F) (+40°C (104 °F) in a non-ventilated enclosure) UL : Maximum surrounding air temperature of 50°C
Lagertemperaturen	-40 (-40 °F) → +80°C (176 °F)
Relative Feuchte	95% max. (no condensation or dripping water)
Max. Betriebshöhe	Operation: 2000 m Transport: 3000 m
Störfestigkeit gegen die Entladung statischer Elektrizität	Immunity to ESD IEC/EN 61000-4-2, level 3
Störfestigkeit gegen hochfrequente Störungen	Immunity to radiated electrostatic fields IEC/EN 61000-4-3, level 3 Immunity to fast transients (burst immunity) IEC/EN 61000-4-4, level 3 Immunity to shock waves IEC/EN 61000-4-5 Radio frequency in common mode IEC/EN 61000-4-6, level 3
Leitungsgebundene und nicht leitungsgebundene Störungen (gemäß EN 55022/11 Kategorie 1)	Class B
Hardware-Kompatibilität	24 VDC base
Maximale Leistungsaufnahme	0.15W @ 3.3V
Schutzart (gemäß IEC/EN 60529)	IP 20
Speicherkapazität	Read / write application and software of connected product
Gewicht	Without packing: 13 g With packing: 19 g
Abmessungen	Without packing: 35 x 36 x 12 mm / 1.38 x 1.42 x 0.47 inch With packing: 80 x 140 x 30 mm / 3.15 x 5.51 x 1.18 inch

**Schemata****Ausmaß (mm)**

Speicherschnittstelle

**Warning:**

The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Crouzet Automatismes SAS and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.