

# › Controllori logici em4 & Millenium Evo Interfaccia

## Interfaccia memoria

- › Copiare il programma applicativo da un PLC a un altro
- › Programmi finali per i vostri clienti
- › Aggiornamento del firmware





Interfaccia memoria

Caratteristiche specifiche	
Codice prodotto	88 980 114
Finitura	Glossy black
Colore	Black RAL 9011
Materie	UL94 V0, 1272/2008/CE (Halogen free)
Caratteristiche generali	
Certificazione prodotti	CE, cURus Listed
Conformità alla direttiva CEM (secondo 2014/30/EU)	IEC/EN 61000-6-1 (Residential, commercial and light-industrial environments) IEC/EN 61000-6-2 (Industrial) IEC/EN 61000-6-3 (Residential, commercial and light-industrial environments) IEC/EN 61000-6-4 (Industrial)
Temperatura di funzionamento	-20 (-4 °F) → +60°C (140 °F) (+40°C (104 °F) in a non-ventilated enclosure) UL : Maximum surrounding air temperature of 50°C
Temperatura di stoccaggio	-40 (-40 °F) → +80°C (176 °F)
Umidità relativa	95% max. (no condensation or dripping water)
Altitudine massima di esercizio	Operation: 2000 m Transport: 3000 m
Resistenza alle scariche elettrostatiche	Immunity to ESD IEC/EN 61000-4-2, level 3
Resistenza alle correnti parassite HF (immunità)	Immunity to radiated electrostatic fields IEC/EN 61000-4-3, level 3 Immunity to fast transients (burst immunity) IEC/EN 61000-4-4, level 3 Immunity to shock waves IEC/EN 61000-4-5 Radio frequency in common mode IEC/EN 61000-4-6, level 3
Emissioni irradiate e condotte (secondo EN 55022/11 gruppo 1)	Class B
Compatibilità hardware	24 VDC base
Potenza assorbita massima	0.15W @ 3.3V
Grado di protezione (secondo CEI/EN 60529)	IP 20
Capacità	Read / write application and software of connected product
Peso	Without packing: 13 g With packing: 19 g
Dimensioni	Without packing: 35 x 36 x 12 mm / 1.38 x 1.42 x 0.47 inch With packing: 80 x 140 x 30 mm / 3.15 x 5.51 x 1.18 inch

Schemi

Ingombro(mm)

Interfaccia memoria



**Warning:**

The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Crouzet Automatismes SAS and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.