

# › Millenium 3 PLC

## Smart Compact CD12/CB12

### With/without display

- › Highly visible blue LCD display with 4 lines of 18 characters, with controllable backlighting
- › Compatible with all the fonctions blocks available on the software
- › Wide temperature range (-20 °C → +70 °C)
- › Analog inputs 0-10 V $\overline{\text{---}}$ , potentiometer, NTC, (0-20mA/Pt100 with adapters)
- › Possibility to set parameters from the front panel



CD12 with display



CB12 without display

Selection guide				
Power supply	Inputs	Outputs	CD12	CB12
12 V $\overline{\text{---}}$	8 digital including 4 analog	4 relays 8A	<b>88974045</b>	
		4 solid state 0.5A including 1 PWM	<b>88974046</b>	-
24 V $\overline{\text{---}}$	8 digital	4 relays 8A	<b>88974041</b>	<b>88974021</b>
		4 solid state 0.5A including 1 PWM	<b>88974042</b>	-
24 V $\sim$	8 digital	4 relays 8A	<b>88974044</b>	<b>88974024</b>
100 → 240 V $\sim$			<b>88974043</b>	<b>88974023</b>

Accessories, Kits & Digital extensions		
Accessories Types	Description	Code
M3 Soft	Programming Software with a complete fonction library	<b>88970111</b>
Physical Accessories	EEPROM memory cartridge	<b>88970108</b>
	3m serial cable: PC → Millenium 3	<b>88970102</b>
	3m USB cable: PC → Millenium 3	<b>88970109</b>
	Millenium 3 → Bluetooth® interface (class A 10m)	<b>88970104</b>

### Our Part-Number System

#### Compact Version



<b>C</b>	<b>D</b>	<b>12</b>
<b>Version</b> C: Compact X: Expandable	<b>Screen</b> D: Whith B: Without	<b>Inputs</b> 10: 6 digital (including 4 analog) 12: 8 digital (including 4 analog) 26: 16 digital (including 6 analog)

You have a project? Contact us on [www.crouzet.com](http://www.crouzet.com)

#### Description:

#### **Millenium 3**: The reference for more than 15 years

The Millenium3 is a versatile, powerful logic controller designed to meet the needs of a wide range of industrial applications. Its ease of use and flexibility make it ideal for automation professionals.

It offers high reliability and accuracy, making it a trusted choice for your automation needs.

For more information about **Millenium 3**: please visit [www.crouzet.com](http://www.crouzet.com)

Accessories, Kits & Digital extensions		
Kit Types	Description	Code
Kit CD12	8 digital (including 4 analog), 4 relays 8 A, 24 V $\overline{\text{DC}}$	88974080
	8 digital, 4 relays 8 A, 100 $\rightarrow$ 240 V $\sim$	88974081
Expansion Modules	Description	Code
<b>Sandwich communication extensions</b>		
<a href="#">XN06</a>	Modbus	88972250
<a href="#">XN05</a>	Ethernet	88970270
<b>Digital sandwich extension</b>		
<a href="#">XE10</a>	24 V $\overline{\text{DC}}$ controller	88970321
	100 $\rightarrow$ 240 V $\sim$	88970323
	24 V $\sim$	88970324
<b>Digital extensions</b>		
<a href="#">XR06</a>	4 digital, 24 V $\overline{\text{DC}}$	88970211
	4 digital, 100 $\rightarrow$ 240 V $\sim$	88970213
	4 digital, 24 V $\sim$	88970214
	4 digital, 12 V $\overline{\text{DC}}$	88970215
<a href="#">XR10</a>	6 digital, 24 V $\overline{\text{DC}}$	88970221
	6 digital, 100 $\rightarrow$ 240 V $\sim$	88970223
	6 digital, 24 V $\sim$	88970224
	6 digital, 12 V $\overline{\text{DC}}$	88970225
<a href="#">XR14</a>	8 digital, 24 V $\overline{\text{DC}}$	88970231
	8 digital, 100 $\rightarrow$ 240 V $\sim$	88970233
	8 digital, 24 V $\sim$	88970234
	8 digital, 12 V $\overline{\text{DC}}$	88970235
<b>Analog extension</b>		
<a href="#">XA03</a>	Analog extension: 3 temperature input	88970800
<a href="#">XA04</a>	Analog extension: 2 inputs/2 outputs	88970241

12 V $\overline{\text{DC}}$ 24 V $\overline{\text{DC}}$ 24 V $\sim$ 100  $\rightarrow$  240 V $\sim$ **General environment characteristics**

Certifications	CE, UL, CSA, GL
Conformity to standards (with the low voltage directive and EMC directive)	IEC/EN 61131-2 (Open equipment) IEC/EN 61131-2 (Zone B) IEC/EN 61000-6-2 IEC/EN 61000-6-3 (*) IEC/EN 61000-6-4 (*): Except configuration (88 970 1X1 or 88 970 1X2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B in a metal enclosure)
Earthing	Not included
Protection rating	In accordance with IEC/EN 60529: IP40 on front panel IP20 on terminal block
Overvoltage category	3 in accordance with IEC/EN 60664-1
Pollution	Degree: 2 in accordance with IEC/EN 61131-2
Max operating Altitude	Operation: 2000 m Transport: 3048 m
Mechanical resistance	Immunity to vibrations IEC/EN 60068-2-6, test Fc Immunity to shock IEC/EN 60068-2-27, test Ea
Resistance to electrostatic discharge	Immunity to ESD IEC/EN 61000-4-2, level 3

	12 V $\overline{\text{DC}}$	24 V $\overline{\text{DC}}$	24 V $\sim$	100 → 240 V $\sim$
Resistance to HF interference	Immunity to radiated electrostatic fields IEC/EN 61000-4-3 Immunity to fast transients (burst immunity) IEC/EN 61000-4-4, level 3 Immunity to shock waves IEC/EN 61000-4-5 Radio frequency in common mode IEC/EN 61000-4-6, level 3 Voltage dips and breaks (a) IEC/EN 61000-4-11 Immunity to damped oscillatory waves IEC/EN 61000-4-12			
Conducted and radiated emissions	Class B (*) in accordance with EN 55022, EN 55011 (CISPR22, CISPR11) group 1 (* ) Except configuration (88 970 1X1 or 88 970 1X2) + (88 970 250 or 88 970 270) + 88 970 241 class A (class B in a metal enclosure)			
Operating temperature Millenium 3 Essential and extensions	-20 → +55 °C (+40 °C in a non-ventilated enclosure) in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2			
Operating temperature Millenium 3 Smart	-20 +70 °C except CB and XB versions in VDC: -30 → +70 °C (+40 °C in a nonventilated enclosure) in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2			
Storage temperature Millenium 3 Essential and extensions	-40 → +70 °C in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2			
Storage temperature Millenium 3 Smart	-40 → +80 °C in accordance with IEC/EN 60068-2-1 and IEC/EN 60068-2-2			
Relative humidity	95 % max. (no condensation or dripping water) in accordance with IEC/EN 60068-2-30			
Mounting	On symmetrical DIN rail, 35 x 7.5 mm and 35 x 15 mm, or on panel (2 x Ø 4 mm)			
Screw terminals connection capacity	Flexible wire with ferrule = conductor: 0.25 to 2.5 mm <sup>2</sup> (AWG 24 → AWG 14) conductors 0.25 to 0.75 mm <sup>2</sup> (AWG 24 → AWG 18) Semi-rigid wire = 1 conductor: 0.2 to 2.5 mm <sup>2</sup> (AWG 25 → AWG 14) Rigid wire = conductor: 0.2 to 2.5 mm <sup>2</sup> (AWG 25 → AWG 14) conductors 0.2 to 1.5 mm <sup>2</sup> (AWG 25 → AWG 16) Tightening torque = 0.5 N.m (4.5 lb-in) (tighten using screwdriver diam. 3.5 mm)			

#### Millenium 3 Essential versions CB, CD

Program size function blocks (FBD)	180 typical bloc 64 macros maximum 256 blocks maximum per macro
Memory size function blocks (FBD)	4 K
Number of lines in Ladder	120 lines
LCD display	XD: Display with 4 lines of 18 characters
Programming method	Function blocks / SCF (Grafcet) or Ladder
Program memory	Flash EEPROM
Removable memory	EEPROM
Data memory	368 bit / 200 words
Back-up time in the event of power failure	Program and settings in the controller: 10 years Program and settings in the plug-in memory: 10 years Data memory: 10 years
Cycle time	FBD: 6 → 90 ms (typically 20 ms) Ladder: typically 20 ms
Response time	Input acquisition time: + 1 to 2 cycle times
Clock data retention	10 years (lithium battery) at 25 °C
Clock drift	Drift < 12 min/year (at 25 °C) 6 s/month (at 25 °C with user-definable correction of drift)
Timer block accuracy	1 % ± 2 cycle times
Start up time on power up	< 1.2 s

	12 V $\overline{\text{DC}}$	24 V $\overline{\text{DC}}$	24 V $\sim$	100 $\rightarrow$ 240 V $\sim$
<b>Characteristics of products with AC power supplied</b>				
<b>Supply</b>				
Nominal voltage	-	-	24 V $\sim$	100 $\rightarrow$ 240 V $\sim$
Operating limits	-	-	-15 % / +20 % or 20.4 $\rightarrow$ 28.8 V $\sim$	-15 % / +10 % or 85 $\rightarrow$ 264 V $\sim$
Supply frequency range	-	-	50/60 Hz (+4 % / -6 %) or 47 $\rightarrow$ 53 Hz / 57 $\rightarrow$ 63 Hz	
Immunity from micro power cuts	-	-	10 ms (repetition 20 times)	
Max. absorbed power	-	-	CB12-CD12: 4 VA	CB12-CD12: 7 VA
Isolation voltage	-	-	1780 V $\sim$	
<b>Inputs</b>				
Input voltage	-	-	24 V $\sim$ (-15 % / +20 %)	100 $\rightarrow$ 240 V $\sim$ (-15 % / +10 %)
Input current	-	-	4.4 mA @ 20.4 V $\sim$ 5.2 mA @ 24.0 V $\sim$ 6.3 mA @ 28.8 V $\sim$	0.24 mA @ 85 V $\sim$ 0.75 mA @ 264 V $\sim$
Input impedance	-	-	4.6 k $\Omega$	350 k $\Omega$
Logic 1 voltage threshold	-	-	$\geq$ 14 V $\sim$	$\geq$ 79 V $\sim$
Making current at logic state 1	-	-	> 2 mA	> 0.17 mA
Logic 0 voltage threshold	-	-	$\leq$ 5 V $\sim$	$\leq$ 20 V $\sim$ ( $\leq$ 28 V $\sim$ : XE10, XR06, XR10, XR14)
Release current at logic state 0	-	-	< 0.5 mA	
Response time with function blocks programming	-	-	Configurable in increments of 10 ms 50 ms min. up to 255 ms State 0 $\rightarrow$ 1 (50/60 Hz)	
Response time with Ladder programming	-	-	50 ms State 0 $\rightarrow$ 1 (50/60 Hz)	
Maximum counting frequency	-	-	In accordance with cycle time (Tc) and input response time (Tr): $1 / (2 \times Tc) + Tr$	
Sensor type	-	-	Contact or 3-wire PNP	
Input type	-	-	Resistive	
Isolation between power supply and inputs	-	-	None	
Isolation between inputs	-	-	None	
Protection against polarity inversions	-	-	Yes	
Status indicator	-	-	On LCD screen for CD	
<b>Characteristics of relay outputs common to the entire range</b>				
Max. breaking voltage	5 $\rightarrow$ 30 V $\overline{\text{DC}}$ 24 $\rightarrow$ 250 V $\sim$			
Breaking current	CB-CD: 8 A			
Electrical durability for 500 000 operating cycles	Utilization category DC-12: 24 V, 1.5 A Utilization category DC-13: 24 V (L/R = 10 ms), 0.6 A Utilization category AC-12: 230 V, 1.5 A Utilization category AC-15: 230 V, 0.9 A			
Max. Output Common Current	12 A for O8, O9, OA			
Minimum switching capacity	10 mA (at minimum voltage of 12 V)			
Minimum load	12 V, 10 mA			
Maximum rate	Off load: 10 Hz At operating current: 0.1 Hz			
Mechanical life	10.000.000 (operations)			
Voltage for withstanding shocks	In accordance with IEC/EN 60947-1 and IEC/EN 60664-1: 4 kV			
Response time	Make 10 ms Release 5 ms			

	12 V $\overline{\text{---}}$	24 V $\overline{\text{---}}$	24 V $\sim$	100 $\rightarrow$ 240 V $\sim$
Built-in protections	Against short-circuits: None Against overvoltages and overloads: None			
Status indicator	On LCD screen for CD			
<b>Characteristics of product with DC power supplied</b>				
<b>Supply</b>				
Nominal voltage	12 V $\overline{\text{---}}$	24 V $\overline{\text{---}}$	-	
Operating limits	-13 % / +20 % or 10.4 $\rightarrow$ 14.4 V $\overline{\text{---}}$ (including ripple)	-20 % / +25 % or 19.2 $\rightarrow$ 30 V $\overline{\text{---}}$ (including ripple)	-	
Immunity from micro power cuts	$\leq$ 1 ms (repetition 20 times)		-	
Max. absorbed power	CB12 with solid state outputs: 1.5 W CD12: 1.5 W	CB12-CD12 with solid state outputs: 3 W	-	
Protection against polarity inversions	Yes		-	
<b>Digital inputs (I1 to IA and IH to IY)</b>				
Input voltage	12 V $\overline{\text{---}}$ (-13 % / +20 %)	24 V $\overline{\text{---}}$ (-20 % / +25 %)	-	
Input current	3.9 mA @ 10.44 V $\overline{\text{---}}$ 4.4 mA @ 12 V $\overline{\text{---}}$ 5.3 mA @ 14.4 V $\overline{\text{---}}$	2.6 mA @ 19.2 V $\overline{\text{---}}$ 3.2 mA @ 24 V $\overline{\text{---}}$ 4.0 mA @ 30.0 V $\overline{\text{---}}$	-	
Input impedance	2.7 k $\Omega$	7.4 k $\Omega$	-	
Logic 1 voltage threshold	$\geq$ 7 V $\overline{\text{---}}$	$\geq$ 15 V $\overline{\text{---}}$	-	
Making current at logic state 1	$\geq$ 2 mA	$\geq$ 2.2 mA	-	
Logic 0 voltage threshold	$\leq$ 3 V $\overline{\text{---}}$	$\leq$ 5 V $\overline{\text{---}}$	-	
Release current at logic state 0	< 0.9 mA	< 0.75 mA	-	
Response time	1 $\rightarrow$ 2 cycle times + 6 ms		-	
Maximum counting frequency	Inputs I1 & I2: FBD (up to 6 kHz) & Ladder (1 kHz) Inputs I3 to IA & IH to IY: In accordance with cycle time (Tc) and input response time (Tr): 1 / ( (2 x Tc) + Tr)		-	
Sensor type	Contact or 3-wire PNP		-	
Conforming to IEC/EN 61131-2	Type 1		-	
Input type	Resistive		-	
Isolation between power supply and inputs	None		-	
Isolation between inputs	None		-	
Protection against polarity inversions	Yes		-	
Status indicator	On LCD screen for CD		-	
<b>Analog or digital inputs (IB to IG)</b>				
CB12-CD12-XD10-XB10	4 inputs IB $\rightarrow$ IE		-	
<b>Inputs used as analog inputs only in FBD</b>				
Measurement range	(0 $\rightarrow$ 10 V) ou (0 $\rightarrow$ V power supply)		-	
Input impedance	14 k $\Omega$	12 k $\Omega$	-	
Input voltage	14.4 V $\overline{\text{---}}$ max.	30 V $\overline{\text{---}}$ max.	-	
Value of LSB	14 mV	29 mV	-	
Input type	Common mode		-	
Resolution	10 bit at max. input voltage		-	
Conversion time	Controller cycle time		-	
Accuracy at 25 °C	$\pm$ 5 %		-	
Accuracy at 55 °C	$\pm$ 6.2 %		-	
Repeat accuracy at 55 °C	$\pm$ 2 %		-	
Isolation between analog channel and power supply	None		-	

	12 V $\overline{\text{---}}$	24 V $\overline{\text{---}}$	24 V $\sim$	100 $\rightarrow$ 240 V $\sim$
Cable length	10 m maximum, with shielded cable (sensor not isolated)			-
Protection against polarity inversions	Yes			-
Potentiometer control	2.2 k $\Omega$ / 0.5 W (recommended) 10 k $\Omega$ max			-
<b>Inputs used as digital inputs</b>				
Input voltage	12 V $\overline{\text{---}}$ (-13 % / +20 %)	24 V $\overline{\text{---}}$ (-20 % / +25 %)		-
Input current	0.7 mA @ 10.44 V $\overline{\text{---}}$ 0.9 mA @ 12 V $\overline{\text{---}}$ 1 mA @ 14.4 V $\overline{\text{---}}$	1.6 mA @ 19.2 V $\overline{\text{---}}$ 2.0 mA @ 24.0 V $\overline{\text{---}}$ 2.5 mA @ 30.0 V $\overline{\text{---}}$		-
Input impedance	14 k $\Omega$	12 k $\Omega$		-
Logic 1 voltage threshold	$\geq$ 7 V $\overline{\text{---}}$	$\geq$ 15 V $\overline{\text{---}}$		-
Making current at logic state 1	$\geq$ 0.5 mA	$\geq$ 1.2 mA		-
Logic 0 voltage threshold	$\leq$ 3 V $\overline{\text{---}}$	$\leq$ 5 V $\overline{\text{---}}$		-
Release current at logic state 0	$\leq$ 0.2 mA	$\leq$ 0.5 mA		-
Response time	1 $\rightarrow$ 2 cycle times			-
Maximum counting frequency in FBD	In accordance with cycle time (Tc) and input response time (Tr): $1 / (2 \times Tc) + Tr$			-
Sensor type	Contact or 3-wire PNP			-
Conforming to IEC/EN 61131-2	Type 1			-
Input type	Resistive			-
Isolation between power supply and inputs	None			-
Isolation between inputs	None			-
Protection against polarity inversions	Yes			-
Status indicator	On LCD screen for CD			-
<b>Characteristics of relay outputs common to the entire range</b>				
Max. breaking voltage	5 $\rightarrow$ 30 V $\overline{\text{---}}$ 24 $\rightarrow$ 250 V $\sim$			
Max. Output Common Current	12 A (10 A UL) for O8, O9, OA			
Breaking current	CB-CD: 8 A			
Electrical durability for 500 000 operating cycles	Utilization category DC-12: 24 V, 1.5 A Utilization category DC-13: 24 V (L/R = 10 ms), 0.6 A Utilization category AC-12: 230 V, 1.5 A Utilization category AC-15: 230 V, 0.9 A			
Minimum switching capacity	10 mA (at minimum voltage of 12 V)			
Minimum load	12 V, 10 mA			
Maximum rate	Off load: 10 Hz At operating current: 0.1 Hz			
Mechanical life	10.000.000 (operations)			
Voltage for withstanding shocks	In accordance with IEC/EN 60947-1 and IEC/EN 60664-1: 4 kV			
Off-cycle response time	Make 10 ms Release 5 ms			
Built-in protections	Against short-circuits: None Against overvoltages and overloads: None			
Status indicator	On LCD screen for CD			
	-			
<b>Digital / PWM solid state outputs</b>				
PWM solid state outputs*	CB12: O4	CD12: O4		-
* Only available with "FBD" programming language	-			
Breaking voltage	10.4 $\rightarrow$ 30 V $\overline{\text{---}}$	19.2 $\rightarrow$ 30 V $\overline{\text{---}}$		-
Nominal voltage	12-24 V $\overline{\text{---}}$	24 V $\overline{\text{---}}$		-
Nominal current	0.5 A			-


	12 V $\overline{\text{---}}$	24 V $\overline{\text{---}}$	24 V $\sim$	100 $\rightarrow$ 240 V $\sim$
Max. breaking current	0.625 A		-	
Voltage drop	$\leq 2$ V for I = 0.5 A (at state 1)		-	
Response time	Make $\leq 1$ ms Release $\leq 1$ ms		-	
Frequency (Hz)	1 Maximum on inductive load		-	
Built-in protections	Against overloads and short-circuits: Yes Against overvoltages (*): Yes Against inversions of power supply: Yes (* In the absence of a voltfree contact between the logic controller output and the load		-	
Min. load	1 mA		-	
Maximum incandescent load	0.2 A / 12 V $\overline{\text{---}}$ 0.1 A / 24 V $\overline{\text{---}}$	0.1 A / 24 V $\overline{\text{---}}$	-	
Galvanic isolation	No		-	
PWM frequency	14.11 Hz 56.45 Hz 112.90 Hz 225.80 Hz 451.59 Hz 1806.37 Hz		-	
PWM cyclic ratio	0 $\rightarrow$ 100 % (256 steps for XD)		-	
PWM accuracy at 120 Hz	< 5 % (20 % $\rightarrow$ 80 %) load at 10 mA		-	
Max. Breaking current PWM	50 mA		-	
Max. cable length PWM	20 m		-	
PWM accuracy at 500 Hz	< 10 % (20 % $\rightarrow$ 80 %) load at 10 mA		-	
Status indicator	On LCD screen for XD		-	
	-		-	

**Schematics**


**Footprint**

**Version**

CD12




CB12



**Input/output wiring**

**Inputs 12 V $\overline{\text{DC}}$ , 24 V $\overline{\text{DC}}$**


Extensions : XN06, XN05, XE10, XR06, XR10, XR14



1	3 wire PNP detector	0-10 V (input set to 0-10 V)	Encoder
2	Contact	Potentiometer attachment (input set to 0-10 V)	Fast digital input
3	Digital input	Potentiometer (input set to potentiometer)	-
4	-	Analogue input	-

**Inputs 100-240 V $\sim$ , 24 V $\sim$**


Extensions: XN06, XN05, XE10, XR06, XR10, XR14



1	Contact	-
2	Digital input	-

**Relay outputs**

Extensions: XE10, XR06, XR10, XR14




1	Contact	-
2	Digital input	-



**Solid state outputs**

Extensions: XA04




1	MOS transistor	-
2	Digital/PWM output	-


**Input/output installations: Bases**

**Inputs**


V~



V ---



**Relay outputs**



**Warning:**

The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. Crouzet and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply, nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.